

# LUB 15-05

---

## Sulphated Fatliquor

### SPECIFICATIONS

Composition	Blend of sulphated natural and synthetic oils.
Appearance	Amber clear liquid.
Active substance	Approx. 55 – 60 %
Charge	Anionic.
pH (10% solution)	Approx.7
Light fastness	Optimum.

### PROPERTIES

LUB 15-05 is a product which offers a very wide use in the main fatliquor of top quality leathers and all types of articles and retannings.

It is especially intended to fatliquor those articles in which high fullness, stretched, clean and springy handled grain is required.

It confers good fullness and smooth feel to leathers surface keeping perfect grain tightness.

Due to LUB 15-05 high light fastness, is especially suitable to manufacture white or light colour leathers.

Moreover it can help to reduce fat spew “repousse” appearance.

### APPLICATION

It is used as a main fatliquor after being neutralized, combining perfectly with any kind of anionic oils such as sulphited, and sulphochlorinated, sulphated and raw oils, emulsified with water 1:3 at 50°C.

### RECOMMENDATIONS

Recommended dose: 2.0 to 9.0% in FATLIQUORING depending on the desired article.

### PACKAGING

120 Kg plactic drum and 1000 Kg IBC

Version 0001 – February 2017

---

Information offered in this publication is based on our knowledge and experience, and it has an indicative purpose. The suitability of the products mentioned can vary depending on the raw material and working conditions. This data do not relieve customers of the responsibility of carrying out their own tests and experiments. We cannot accept responsibility for the use of the product, which must be verified and evaluated by the customer.